

# Methyl Bromide 0.5/a

Order No. 81 01 671

## Application Range

Standard Measuring Range:	5 to 30	/ 0.5 to 5 ppm
Number of Strokes n:	2	/ 8
Time for Measurement:	approx. 2 min	/ approx. 5 min
Standard Deviation:	± 15 to 20 %	
Color Change:	white → blue green	

## Ambient Operating Conditions

Temperature:	2 to 40 °C
Absolute Humidity:	max. 20 mg H <sub>2</sub> O / L

## Reaction Principle

- a)  $\text{CH}_3\text{Br} + \text{H}_2\text{S}_2\text{O}_7 \rightarrow \text{HBr}$   
 b<sub>1</sub>)  $\text{HBr} + \text{Cr}^{\text{VI}} \rightarrow \text{Br}_2$   
 b<sub>2</sub>)  $\text{Br}_2 + \text{o-tolidine} \rightarrow \text{blue green reaction product}$

## Cross Sensitivity

Vinyl chloride:	2 ppm no reading.
Carbon tetrachloride:	2 ppm no reading
Perchloroethylene and Trichloroethylene:	5 ppm changes the indicating layer to a light yellow.
1,2-dichloroethylene:	20 ppm result in a reading of approx. 3 ppm.
1,1-dichloroethylene:	up to 2 ppm the sensitivity is the same as with methyl bromide.



D-5449-2014